

Part No.: 182TH

Applications:

This document establishes the specifications for a two conductor unshielded non-plenum cable used for power limited applications.

Construction Details:

Number of Conductors: 2/C

Conductor: 18AWG Solid Bare Copper. Insulation material: Polyvinyl Chloride.

Color code: Red, White

Jacket material: Polyvinyl Chloride Jacket Color: UV Resistant Brown Nominal Diameter: 0.148 in.

Electricals:

Suggested Working Voltage: Voltage Not Specified

Technical Details:


Temperature Rating

Operation -20°C to +60°C

Nominal Weight: 17 lbs. / 1,000 ft.

18-2 Unshielded Non-Plenum

ETL listed for guaranteed performance



Standards:

- National Electric Code—Article 725
- UL Subject 13, Type CL2

Codes & Listings:

• (ETL)US CL2

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



18-2 Unshielded Non-Plenum

ETL listed for guaranteed performance

Part No.: 182TH

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.