

Part No.: 188TH

Applications:

This document establishes the specifications for an eight conductor unshielded non-plenum cable used for power limited applications.

Construction Details:

Number of Conductors: 8/C

Conductor: 18AWG Solid Bare Copper. Insulation material: Polyvinyl Chloride. Color code: Red, White, Green, Blue, Yellow,


Brown, Orange, Black

Jacket material: Polyvinyl Chloride Jacket Color: UV Resistant Brown Nominal Diameter: 0.218 in.

Electricals:

Suggested Working Voltage: Voltage Not Specified

18-8 Unshielded Non-Plenum



Technical Details:

Temperature Rating

Operation -20°C to +60°C

Nominal Weight: 52 lbs. / 1,000 ft.

Standards:

- National Electric Code—Article 725
- UL Subject 13, Type CL2

Codes & Listings:

UL or ETL

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



18-8 Unshielded Non-Plenum

Part No.: 188TH

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.