

# Category 6E Enhanced 550 MHz Non-Plenum

ETL verified for guaranteed performance

Part No.: 6RNS

## Applications

Supports all category 6 applications including Ethernet 1000BASE-TX, 100BASE-VG and 155 ATM. Particularly suited for high bandwidth applications with anticipated data rates to 3.2 Gbps.

## Construction Details:


No. 23 AWG solid bare copper conductor insulated with polyethylene. Two colored mated insulated conductors twisted together to form a pair and four pairs assembled to form a core. The core is jacketed with a flame retardant PVC.

## Color Code:

Pair	Color Code
1	Blue with White
2	Orange with White
3	Green with White
4	Brown with White

## Electrical Parameters:

Mutual Capacitance:	14 pF/ft nominal
Capacitance Unbalance:	330 pF/ft maximum
Velocity of Propagation:	70%
Max. Conductor D.C.R.:	28.6 ohm/1000 feet
Max. DCR Unbalance:	3%
Max. Delay Skew:	18.0 ns/100m
Characteristic Impedance:	from 0.772 - 100 MHz 100Ω ± 15%
	from 101 - 250 MHz 100Ω ± 22%
	from 251 - 550 MHz 100Ω ± 32%



## Technical Details

Temperature Rating	
Installation	0°C to 50°C
Operation	-10°C to 60°C
Nominal Diameter	0.200 in.
Nominal cable weight:	30 lb/1000 feet


## Standards

- ANSI/TIA/EIA 568C.2 Category 6
- UL Subject 444
- IEEE 802.3af

## Codes & Listings

- UL 1666: CMR rating FT4
- ETL Electrically Verified to ANSI/TIA/EIA 568C.2 Category 6
- C(ETL)US CMR






# Category 6E Enhanced 550 MHz Non-Plenum

ETL verified for guaranteed performance

Part No.: 6RNS

**Note:** While Remeee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeee Products Corp. does not guarantee that it is error-free, nor does Remeee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.





# Category 6E Enhanced 550 MHz Non-Plenum

ETL verified for guaranteed performance

Part No.: 6RNS

## Electrical Characteristics:

Frequency	Return Loss	Attenuation	NEXT	PS-NEXT	ELFEXT	PS-ELFEXT	ACR	PS-ACR
	dB	dB(100m)	dB	dB	dB	dB	dB	dB
MHz	Minimum	Maximum	Minimum	Minimum	Minimum	Minimum	Minimum	Minimum
1	20.0	2.0	80.3	78.3	73.8	70.8	78.3	76.3
4	23.0	3.8	71.3	69.3	61.8	58.8	67.5	65.5
10	25.0	6.0	65.3	63.3	53.8	50.8	59.3	57.3
16	25.0	7.6	62.2	60.2	49.7	46.7	54.6	52.6
20	25.0	8.5	60.8	58.8	47.8	44.8	52.3	50.3
31.25	23.6	10.7	57.9	55.9	43.9	40.9	47.2	45.2
62.5	21.5	15.4	53.4	51.4	37.9	34.9	38.0	36.0
100	20.1	19.8	50.3	48.3	33.8	30.8	30.5	28.5
200	18.0	29.0	45.8	43.8	27.8	24.8	16.8	14.9
250	17.3	32.8	44.3	42.3	25.8	22.8	11.5	9.5
300	16.8	36.4	43.1	41.1	24.3	21.3		
350	16.3	39.8	42.1	40.1	22.9	19.9		
400	15.9	43.0	41.3	39.3	21.8	18.8		
500	14.8	49.5	40.2	38.2	20.0	17.0		
550	14.4	53.1	39.5	37.5	18.9	15.9		

\*Values above 250 MHz are for engineering information only

### Preparation For Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

