

RG11Quad Coaxial Cable Plenum

Part No.: 725109

ETL listed for guaranteed performance
Made in the USA

Applications


This document establishes the specifications for a plenum rated RG11/U, 75 ohm, coaxial cable used for computers, broadcast, and instrumentation applications.

Construction Details

Center Conductor: 14AWG Solid Bare Copper
 Dielectric Material: Foamed FEP
 Nominal Dielectric Core OD: 0.280 in.
 1st Shield: Aluminum/Polyester Tape (100% coverage)
 2nd Shield: Aluminum Braid
 3rd Shield: Aluminum/Polyester Tape (100% coverage)
 4th Shield: Aluminum Braid
 Jacket Material: Remguard Plenum Polymer
 Nominal Overall Diameter: 0.405 in.
 Jacket Color: Per Customer Requirement
 Surface Print: 3122598 CMP RG11/U TYPE 14AWG C(ETL)US
 + Sequential Footage Marking

Electricals

Nominal Capacitance: 17.3 pF/ft.
 Nominal Characteristic Impedance: 75 Ω
 Nominal Velocity of Propagation: 78%
 Nominal Attenuation per 100 ft.:
 1.5 dB @ 100 MHz
 2.2 dB @ 200 MHz
 3.7 dB @ 500 MHz



Technical Details

Temperature Rating	Operation: -2°C to +60°C
Nominal Weight:	75 lbs. / 1,000 ft.

Standards

- NEC Article 800
- Type CMP


Codes & Listings

- C(ETL)US CMP

Preparation For Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





RG11Quad Coaxial Cable Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 725109

Note: While Remeë Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeë Products Corp. does not guarantee that it is error-free, nor does Remeë Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeë Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeë Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

