

This document establishes the specifications for a

plenum rated two conductor unshielded cable


used for communication applications

## Part No.: 725180

**Applications:** 

# 18-2 Unshielded Plenum

ETL listed for guaranteed performance Made in the USA



### **Technical Details:**

**Temperature Rating** 

-2°C to +60°C Operation:

Nominal Weight:	17 lbs. / 1,000 ft.
Max. Rec. Pulling	45 lbs.

### Standards:

- NEC Article 800, 760
- CMP/FPLP Rating FT6

### **Codes & Listings:**

C(ETL)US CMP

### **Preparation for Shipment:**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



l ension:

**Construction Details:** 

Number of Conductors: 2/C Conductor: 18AWG Stranded Bare Copper Insulation Material: Ramguard Plenum Polymer Nominal Insulation Thickness: 0.007 in. Nominal Insulation Diameter: 0.060 in. Color Code: Black. Red Jacket Material: Remguard Plenum Polymer Nominal Jacket Thickness: 0.015 in. Nominal Diameter: 0.150 in. Surface Print: 3122598 CMP/FPLP 18AWG C(ETL)US FT6 MADE IN USA + Sequential Footage Marking

### **Electricals:**

Suggested Working Voltage: 300 Volts, rms.

DCR @ 20°C: 6.5 ohms/1M'



# 18-2 Unshielded Plenum

ETL listed for guaranteed performance Made in the USA

## Part No.: 725180

**Note:** While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

