

# 14-4 Unshielded Plenum

ETL listed for guaranteed performance Made in the USA

Part No.: 760144

## **Applications:**

This document establishes the specifications for a four conductor unshielded plenum cable used for fire protective signaling circuit applications.

## **Construction Details:**

Number of Conductors: 4/C Conductor: 14AWG Solid Bare Copper Insulation Material: Remguard Plenum Polymer Nominal Insulation Thickness: 0.013 in. Nominal Insulation Diameter: 0.090 in. Color Code: Black, Red, White, Green Jacket Material: Remguard Plenum Polymer Jacket Color: Red or Per Customer Requirement Nominal Jacket Thickness: 0.015 in. Nominal Diameter: 0.250 in. Surface Print: 3122598 FPLP 14AWG (ETL)US + Sequential Footage Marking


#### **Electricals:**

Suggested Working Voltage: 300 Volts, rms.

#### **Technical Details:**

Temperature Rating

	Operation	-2°C to +75°C
Nominal Weight:		69 lbs. / 1,000 Feet



# Standards:

- NEC Article 760
- UL Subject 1424, Type FPLP

# **Codes & Listings:**

• (ETL)US

## **Preparation for Shipment:**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.







# 14-4 Unshielded Plenum

ETL listed for guaranteed performance Made in the USA

# Part No.: 760144

**Note:** While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

