

Part No.: 760164

16-4 Unshielded Plenum

ETL listed for guaranteed performance
Made in the USA

Applications:

This document establishes the specifications of a four conductor unshielded cable used for communications and power limited applications.

Construction Details:

Number of Conductors: 4/C

Conductor: 16AWG Solid Bare Copper

Insulation Material: Remguard Plenum Polymer

Nominal Insulation Thickness: 0.010 in. Nominal Insulation Diameter: 0.070 in. Color Code: Black, Red, Green, White Jacket Material: Renguard Plenum Polymer Jacket Color: Red or Per Customer Requirement

Nominal Jacket Thickness: 0.015 in.

Nominal Diameter: 0.200 in.

Surface Print: 3122598 FPLP 16AWG (ETL)US +

Sequential Footage Marking

Electricals:


Suggested Working Voltage: 300 Volts, rms.

Technical Details:

Temperature Rating

Operation: -2°C to +60°C

Nominal Weight: 43 lbs. / 1,000 Feet



Standards:

- NEC Article 760
- UL Subject 1424, Type FPLP

Codes & Listings:

(ETL)US

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.







16-4 Unshielded Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 760164

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.



