

Part No.: 900912WBTPOLY

Applications:

This document establishes the specifications of a two conductor shielded cable with a water block tape and polyethylene jacket suitable for outdoor and direct burial use.


Construction Details:

Number of Conductors:2 Conductor: 18AWG Stranded Bare Copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.008 in. Nominal Insulation Diameter: 0.062 in. Color Code: Black, White Shielding: Aluminum/Polyester Tape (100% Coverage, Foil and Drain In) Drain: Stranded Tin Copper Tape: Water Block Tape Jacket Material: Polyethylene Jacket Color: Black Nominal Jacket thickness: 0.025 in. Nominal Diameter: 0.206 in. Surface Print: REMEE PRODUCTS 18AWG 2 COND + Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 Volts, rms.

18-2 Shielded Non-Plenum



Technical Details:

Temperature Rating

	Operation:	-20°C to +60°C
Nominal Weight:		22 lbs. / 1,000 feet

Codes & Listings:

Non Listed

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





18-2 Shielded Non-Plenum

Part No.: 900912WBTPOLY

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

