

Part No.: 900913R

# 18-3 Shielded Non-Plenum

ETL listed for guaranteed performance

Made in the USA

# Applications:

This document establishes the specifications for a three conductor shielded cable used for communication applications.

#### **Construction Details:**

Number of Conductors: 3/C

Conductor: 18AWG Stranded Bare Copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.008 in. Nominal Insulation Diameter: 0.062 in.

Color Code: Black, White, Red

Shielding: Overall Aluminum/Polyester (100% coverage)

Drain: Stranded Tin Copper Jacket Material: Polyvinyl Chloride Nominal Jacket Thickness: 0.015 in.

Nominal Diameter: 0.200 in.

Surface Print: 3122598 CMR 18AWG C(ETL)US FT4 + Sequential Footage Marking

#### **Electricals:**


Suggested Working Voltage: 300 Volts, rms.

### **Technical Details:**

**Temperature Rating** 

Operation: -20°C to +60°C

Nominal Weight: 26 lbs. / 1,000 feet



#### Standards:

- NEC Article 800
- UL Subject 444
- CMR Type FT4

### **Codes & Listings:**


C(ETL)US CMR FT4

## **Preparation for Shipment:**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.







# 18-3 Shielded Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 900913R

**Note:** While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.



