

## Part No.: CH1023F

#### **Applications:**

This document establishes the specifications for a four conductor cable used in communication applications

#### **Construction Details:**

Number of Conductors: 4/C Conductor: 16 AWG 65/34 Bare Copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.012 in. Nominal Insulation Diameter: 0.080 in. Color Code: Black, Red, White, Green Jacket Material: Polyvinyl Chloride Nominal Jacket Thickness: 0.018 in. Nominal Diameter: 0.238 in Surface Print: 3122598 HI-STRAND AUDIO CABLE 4 COND 16AWG 65 STRAND CMR/CL3R 75°C C(ETL)US FT4 MADE IN USA...SUITABLE FOR OUTDOOR **USE...OXYGEN FREE COPPER** + Sequential Footage Marking

#### **Electricals:**

Suggested Working Voltage: 300 Volts, rms.

#### **Technical Details:**


Temperature Rating

Operation -20°C to +75°C

Nominal Weight: 50 lbs. / 1,000 Feet

# 16-4 Unshielded Audio Cable Non-Plenum

ETL listed for guaranteed performance Made in the USA



#### Standards:

- NEC Article 800
- UL Subject 444, Type CMR/CL3R FT4

### Codes & Listings:

C(ETL)US Type CMR/CL3R FT4

#### **Preparation for Shipment:**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.







## Part No.: CH1023F

## 16-4 Unshielded Audio Cable Non-Plenum

ETL listed for guaranteed performance Made in the USA

**Note:** While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.



