

Part No.: LUGRX46LP

Applications:

This document establishes the specifications for a composite cable used for power limited applications.

Construction Details:

Number of Conductors: 2/C (1 pair) Conductor: 22AWG Stranded Bare Copper Insulation Material: FEP Nominal Insulation Thickness: 0.012 in. Nominal Insulation Diameter: 0.053 in. Color Code: White paired with Green Shield: Aluminum/Polyester Tape (100% Coverage) Drain: Tin Copper

Number of Conductors: 1/C Conductor: 18AWG Stranded Bare Copper Insulation Material: Remguard Nominal Insulation Thickness: 0.008 in. Nominal Insulation Diameter: 0.062 in. Color Code: Orange

Number of Conductors: 2/C Conductor: 12AWG Stranded Bare Copper Insulation Material: Remguard Nominal Insulation Thickness: 0.009 in. Nominal Insulation Diameter: 0.118 in. Color Code: Red, Black

Jacket Material: Remguard Jacket Color: Per Customer Requirement Nominal Diameter: 0.325 in. Surface Print: 3122598 CL3P 2C12 2C22 1C18 (ETL)US + Sequential Footage Marking

22-2 Shielded 18-1 Unshielded 12-2 Unshieled Plenum

Electricals:

Suggested Working Voltage: 150 V RMS

Max. Capacitance Cond-Cond: 25pF/FT

Technical Details:

Temperature Rating

Operation -2°C to +75°C

Nominal Weight: 72 Lbs. / 1,000 ft.

Standards:

- National Electric Code Article 725
- UL Subject 13

Codes & Listings:

• (ETL)US CL3P

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





22-2 Shielded 18-1 Unshielded 12-2 Unshieled Plenum

Part No.: LUGRX46LP

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

