

Part No.: R001006WBTPOLY

## **Applications:**

This document establishes the specifications for a two conductor unshielded cable with a water swellable tape and polyethylene jacket used for audio, and remote control applications, suitable for outdoor and direct burial use, sunlight resistant.

#### **Construction Details:**

Number of Conductors: 2/C

Conductor: 18AWG Stranded Bare Copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.008 in. Nominal Insulation Diameter: 0.062 in.

Color Code: Black, Red Tape: Water Swellable Tape

Jacket Material: UV Resistant Polyethylene Nominal Jacket Thickness: 0.020 in. Nominal Diameter: 0.184 in. ± 0.010 in.

Rip Cord: Nylon

Surface Print: REMEE PRODUCTS 18AWG 2

CONDUCTOR + Sequential Footage


Marking

#### **Electricals:**

Maximum Working Voltage: 300 Volts, rms.

# 18-2 Unshielded Polyethylene

Made in the USA



#### **Technical Details:**

**Temperature Rating** 

Operation -20°C to +60°C.

Nominal Weight: 17 lbs. / 1,000 feet

### **Codes & Listings:**

Non-Listed

## **Preparation for Shipment:**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





# 18-2 Unshielded Polyethylene

Made in the USA

Part No.: R001006WBTPOLY

**Note:** While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

