

Part No.: R001531WBTPOLY

Applications

This document establishes the specifications for an RG 6/U Type 75 ohm coaxial cable with a waterblocking tape and polyethylene jacket used for video display, point-of-sale terminals, Local Area Network Controls, and CCTV Broadcasting applications, suitable for outdoor applications.

Construction Details

Center Conductor: 18AWG Solid Bare Copper Dielectric Material: Cellular Polyethylene Nominal Dielectric Core O.D: 0.180 in.

Shield: CCA Braid
Tape: Waterblocking Tape
Jacket Material: Polyethylene
Nominal Overall Diameter: 0.275 in.
Jacket Color: Per Customer Requirement

Surface Print: RG6 SUITABLE FOR DIRECT BURIAL/WET

LOCATIONS + Sequential Footage Marking


Electricals

Nominal Capacitance: 17.3 pF/ft

Nominal Characteristic Impedance: 75 ohms Nominal Velocity of Propagation: 78% Nominal Attenuation per 100 feet:

0.7 dB @ 10 MHz 1.5 dB @ 50 MHz 2.1 dB @ 100 MHz 4.5 dB @ 400 MHz 8.1 dB @ 1000 MHz

RG-6/U Coaxial Cable Polyethylene Jacket



Technical Details

Temperature Rating

Operation: -20°C to +60°C

Nominal Weight: 42 lbs. / 1,000 feet

Codes & Listings

Non-Listed

Preparation For Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





RG-6/U Coaxial Cable Polyethylene Jacket

Part No.: R001531WBTPOLY

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

