

Part No.: R00308

14-4 Shielded Non-Plenum

ETL listed for guaranteed performance

Made in the USA

Applications:

This document establishes the specifications for a riser rated four conductor shielded cable used for fire protective signaling circuit applications.

Construction Details:

Number of Conductors: 4/C

Conductor: 14AWG Solid Bare Copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.014 in Nominal Insulation Diameter: 0.092 in Color Code: Black, Red, White, Green

Shielding: Overall Aluminum/Polyester (100% Coverage)

Drain: Solid tinned copper

Jacket Material: Polyvinyl Chloride Nominal Jacket thickness: 0.015 in

Nominal Diameter: 0.264 in

Surface Print: 3122598 FPLR 14AWG (ETL)US +

Sequential Footage Mark

Electricals:

Maximum Working Voltage: 300 Volts, rms.

Technical Details:

Temperature Rating

Operation: -20°C to +60°C

Nominal Weight: 74 lbs. / 1,000 feet

Standards:

- NEC Article 760
- UL Subject 1424, Type FPLR

Codes & Listings:

• (ETL)US

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.







14-4 Shielded Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: R00308

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.



