



Category 5e + 16/4 Siamese Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: RMMS5AE350+1023

Applications:

This document establishes the specifications for a cable containing one Category 5e and a four conductor 16AWG cable in a siamese construction with a polyvinyl chloride jacket.

4c16 Construction Details:

Conductor: 16AWG Stranded Bare Copper
Number of Conductors: 4/C
Insulation Material: Polyvinyl Chloride
Insulation Color: Black, Red, Green, White

Cat5e Construction Details:

Conductor: 24AWG Solid Bare Copper.
Number of Conductors: 4 Pairs (8/C)
Insulation Material: Polyethylene.

Overall Cable Construction Details:

Construction Type: One Cat5e and one 4c16AWG are pulled in parallel at extrusion in a siamese construction.

Jacket Material: Polyvinyl Chloride
Jacket Color: Yellow

Surface Print: 4P24 ETL VERIFIED CAT5E 4C16 65
STRAND 3122598 CM C(ETL)US MADE IN USA

Nominal Jacket Thickness: 0.025 in.

Nominal Overall Diameter: Minor over Cat5e: 0.220 in.
Minor over 4c16: 0.242 in.
Major: 0.487 in.

Standards:

- NEC Article 800
- ANSI/TIA/EIA 568C.2 Category 5e

Codes & Listings:

- CM Rating
- C(ETL)US

Electrical Parameters (Cat5e):

Nominal Mutual Capacitance:	14 pF/ft
Maximum Capacitance Unbalance:	330 pF/ft
Velocity of Propagation:	70%
Max. Conductor D.C.R.:	28.6 ohm/1000 feet
Max. DCR Unbalance:	5%
Max. Delay Skew:	45.0 ns/100m
Characteristic Impedance:	from 0.772 - 100 MHz 100 ± 15%
	from 101 - 250 MHz 100 ± 22%
	from 251 - 350 MHz 100 ± 32%





Category 5e + 16/4 Siamese Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: RMMS5AE350+1023

Electrical Characteristics (Cat5e):

Frequency	SRL	Return Loss	Attenuation	NEXT	PS-NEXT	ELFEXT	PS-ELFEXT	ACR	PS-ACR
	dB	dB	dB(100m)	dB	dB	dB	dB	dB	dB
MHz	Minimum	Minimum	Maximum	Minimum	Minimum	Minimum	Minimum	Minimum	Minimum
1	23.0	20.0	2.0	65.3	62.3	63.8	60.8	63.3	60.3
4	23.0	20.3	4.0	56.3	53.3	51.7	48.7	52.3	49.3
8	23.0	20.5	5.7	51.8	48.8	45.7	42.7	46.1	43.1
10	23.0	25.0	6.4	50.3	47.3	43.8	40.8	43.9	40.4
16	23.0	25.0	8.2	47.3	44.3	39.7	36.7	39.1	36.1
20	23.0	25.0	9.2	45.8	42.8	37.7	34.7	36.6	33.6
25	22.0	25.0	10.4	44.3	41.3	35.8	32.8	33.9	30.9
31.25	21.1	23.6	11.7	42.9	39.9	33.9	30.9	31.2	28.2
62.5	18.1	21.5	16.9	38.4	35.4	27.8	24.8	21.5	18.5
100	16.0	20.1	21.9	35.3	32.3	23.8	20.8	13.4	10.4
250	12.0	17.3	36.8	34.3	32.3	15.8	12.8	----	----
300	11.2	16.8	40.9	33.2	31.2	14.2	11.2	----	----
350	10.6	16.3	44.8	32.2	30.2	12.9	9.9	----	----


Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



MADE IN THE USA





Category 5e + 16/4 Siamese Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: RMMS5AE350+1023

Note: While Remeo Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeo Products Corp. does not guarantee that it is error-free, nor does Remeo Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeo Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeo Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.



MADE IN THE USA

