

# CAMPLEX®

## BROADCAST FIBER OPTIC SOLUTIONS

### Complex CMX-DVI-TR Singlemode/Multimode Fiber Extender

#### CMX-DVI-TR TRANSMITTER

- 1 Power LED
- 2 EDID LED
- 3 EDID Reset
- 4 Fiber Connection
- 5 Power Adapter Connection
- 6 DVI Input—Connect to Source



#### EDID Learning Mode

1. Turn the display on and connect the transmitter.
2. Press the EDID button on the transmitter. LED will light blue.
3. Light will go out in 5 seconds when EDID learning is complete.

#### CMX-DVI-TR RECEIVER

- 1 Power LED
- 2 Signal LED
- 3 Fiber Connection
- 4 Power Adapter Connection
- 5 DVI Output—Connect to Display



#### SYSTEM SET UP



#### SPECIFICATIONS

Compliance	DVI-D
Transmission Distance	4921 feet singlemode / 984 feet multimode
Max Resolution	1920 x 1200 @60Hz
Video Bandwidth	1.65 Gbps
Dimensions	2.6 x 1.5 x 0.6 in
Weight	0.36 lb

<b>Includes</b>
Two 5DC/2A Power Supplies
One DVI Transmitter with EDID
One DVI Receiver

