

#2355 Tinned Copper Flat Braid (Mil Spec QQ-B-575 & A-A-59569)

Tinned copper shielding flat braid manufactured round per Mil Spec QQ-B-575 and A-A-59569.

- Soft annealed tinned copper braid tightly woven, rolled flat at manufacture, extremely flexible
- Useful as battery grounding, bonding strap for aircraft, vehicles, marine equipment. Eliminates ignition interference.
- Woven tinned copper with strands meeting ASTM-B-33. This series is RoHS compliant.

Daburn Part Number	Nom. Flat Width	QQ-B-575 Mil Spec	A-A-59569 Mil Spec	Construction	AWG Equivalent	Nominal CMA	Nom. Amps
2355-1/40	.025"	-	-	18-1-36	27	200	4
2355-1/32	1/32"	-	-	16-1-36	24	400	6
2355-3/64	3/64"	-	-	12-2-36	22	600	7
2355-3/64A	3/64"	QQB575F36T0031	AA59569F36T0031	24-1-36	22	600	7
2355-1/16	1/16"	-	-	16-3-36	20	1200	11
2355-3/32	3/32"	-	-	16-3-36	19	1200	11
2355-3/32A	3/32"	QQB575F36T0062	AA59569F36T0062	24-2-36	19	1200	11
2355-7/64	7/64"	-	-	16-4-36	18	1600	16
2355-1/8	1/8"	QQB575F36T0078	AA59569F36T0078	24-3-36	18	1800	16
2355-5/32	5/32"	QQB575F36T0109	AA59569F36T0109	24-4-36	16	2400	19
2355-3/16	3/16"	QQB575F36T0125	AA59569F36T0125	24-5-36	15	3000	25
2355-1/4	1/4"	QQB575F36T0171	AA59569F36T0171	24-7-36	14	4200	32
2355-1/4A	1/4"	QQB575F36T0156	AA59569F36T0156	24-10-36	12	6000	40
2355-9/32	9/32"	QQB575F36T0203	AA59569F36T0203	24-13-36	11	7800	46
2355-3/8	3/8"	-	-	48-4-36	12	7200	46
2355-3/8A	3/8"	-	-	48-6-36	12	7200	60
2355-3/8B	3/8"	-	-	24-5-30	9	12000	40
2355-1/2	1/2"	-	-	48-8-36	10	9600	53
2355-1/2A	1/2"	QQB575F30T0437	AA59569F30T0437	24-10-30	6	24000	93
2355-5/8	5/8"	QQB575F36T0375	AA59569F36T0375	48-8-36	10	9600	53
2355-5/8A	5/8"	QQB575F30T0500	AA59569F30T0500	24-15-30	5	36000	120
2355-5/8B	5/8"	QQB575F36T0500	AA59569F36T0500	48-11-36	9	13200	62
2355-3/4	3/4"	QQB575F36T0781	AA59569F36T0781	48-18-36	7	21600	85
2355-3/4A	3/4"	-	-	24-67-36	4	40200	125
2355-3/4B	3/4"	-	-	48-5-30	6	24000	93
2355-3/4C	3/4"	-	-	24-20-30	3	48000	145
2355-25/32	13/16"	-	-	48-19-36	7	22800	93
2355-7/8	7/8"	-	-	48-22-36	6	26400	105
2355-7/8A	7/8"	-	-	24-24-30	3	57600	165
2355-7/8B	7/8"	-	-	48-12-30	2	57600	150
2355-15/16	15/16"	-	-	24-26-30	2	62400	170
2355-15/16A	15/16"	-	-	24-27-30	2	64800	175
2355-1"	1"	-	-	48-18-36	7	21600	85
2355-1A	1"	-	-	48-8-30	8	38400	120
2355-1B	1"	-	-	24-32-30	1	76800	195
2355-1 1/4"	1 1/4"	-	-	48-10-30	10	48000	145
2355-1 3/8"	1 3/8"	QQB575F30T0875	AA59569F30T0875	48-7-30	5	33600	100
2355-1 3/8A	1 3/8"	-	-	48-14-30	2	67200	165
2355-1 3/8B	1 3/8"	-	-	48-22-30	1/0	105600	235
2355-1 1/2	1 1/2"	QQB575F30T1375	AA59569F30T1375	48-11-30	3	52800	145
2355-1 1/2A	1 1/2"	-	-	48-16-30	1	76800	180
2355-1 5/8	1 5/8"	-	-	48-18-30	1	86400	200
2355-1 5/8A	1 5/8"	-	-	48-84-36	1	100800	230
2355-1 3/4"	1 3/4"	-	-	48-26-30	2/0	124800	250
2355-2	2"	-	-	48-32-30	3/0	153600	290
2355-2A	2"	-	-	48-28-30	2/0	134400	255
2355-2 1/4"	2 1/4"	-	-	48-35-30	3/0	168000	320
2355-2 3/8"	2 3/8"	-	-	48-44-30	4/0	211200	370
2355-2 1/2"	2 1/2"	-	-	48-52-30	250 MCM	249600	410
2355-3"	3"	-	-	48-47-30	4/0	225600	390