

## Daburn #2419 – PFA High Temperature Wire UL Style 1727

Daburn PFA High Temperature Wire has the following characteristics:

- Very Good Mechanical Strength and Abrasion Resistance
- Excellent Electrical Insulating Properties
- Excellent Thermal Stability
- Resistant to Chemicals and Solvents
- Heat, Age, & Ozone Resistant
- Good Flexibility
- Thin Walls for Weight and Space Savings
- Good Lubricity (low coefficient of friction)

Suitable for use as internal wiring in appliances and electronic equipment. This wire meets UL Style 1727.

**Description:** Single conductor stranded nickel plated copper insulated with extruded PFA insulation.

**Operating Temperature:** -65°C to +250°C

**Voltage Rating:** 600 Volts UL

This series is RoHS compliant.

Catalog Number	AWG	Strand	Nom. Wall		Nom. O.D.	
			Inches	mm	Inches	mm
2419/14	14	19/27	.020	0.51	.111	2.82
2419/16	16	19/29	.020	0.51	.097	2.46
2419/18	18	19/30	.020	0.51	.091	2.31
2419/20	20	19/32	.020	0.51	.081	2.06
2419/22	22	7/30	.020	0.51	.073	1.85
2419/24	24	7/32	.020	0.51	.067	1.70

**Colors Available:** Black, Red, White, Green, Yellow, Blue, Brown, Grey, Violet, Orange  
Tinned Plated & Silver plated copper conductors also available. Call to inquire.