



High Voltage XLPE Wire - UL3239, 105°C, VW-1



Description: One stranded Tinned Copper (TC) conductor, extruded flexible High Density Polyethylene (HDPE) insulation and a white cross-linked polyethylene XLPE jacket. Recognized by UL as style 3239.

Please call for colors other than white. This series is low smoke, non-halogen and RoHS and REACH compliant. Standard put-ups are 100 feet or 1000 feet.

Twisted pair and multi-core versions available to order.

Daburn Cat. No.	AWG	Stranding	HDPE Insulation Wall (Inches)	XLPE Jacket Wall (Inches)	Voltage (KVDC)	Nom. O.D. (Inches)
2639/24A	24	19/36	.0217	.0217	20	.111
2639/24D	24	19/36	.0413	.0413	40	.189
2639/22A	22	19/34	.0217	.0217	20	.117
2639/22D	22	19/34	.0413	.0413	40	.195
2639/20A	20	24/34	.0217	.0217	20	.124
2639/20D	20	26/34	.0413	.0413	40	.203
2639/18A	18	19/30	.0217	.0217	20	.132
2639/18D	18	19/30	.0413	.0413	40	.213
2639/16A	16	26/30	.0217	.0217	20	.146
2639/16D	16	26/30	.0413	.0413	40	.224
2639/14A	14	41/30	.0217	.0217	20	.161
2639/14D	14	41/30	.0413	.0413	40	.240