



#2725 – Extra-Flexible PVC Hook-Up Wire UL 10093, 3,000V AC, 105°C, VW-1

Daburn UL 10093 PVC Hook-Up Wire exhibits the following characteristics:

- Good Mechanical Strength and Abrasion Resistance
- Good Electrical Insulating Properties
- Excellent Thermal Stability
- Good Low Temperature Softness & Flexibility
- Resistant to Chemicals
- Good dielectric properties
- Excellent Resistance to Ozone and Oxidation
- Very Good Flexibility

Description: Single conductor stranded tinned copper insulated with PVC insulation. This construction allows for a uniform, flexible, concentric, quality construction.

Operating Temperature: -40°C to +105°C

Voltage Rating: 3,000 Volts AC

VW-1 & FT1

UL Style 10093

This series is RoHS compliant.

Catalog Number	AWG	Strand	Nom. Wall		Nom. O.D.		Conductor Resistance 20°C Ohm/mft
			Inches	mm	Inches	mm	
2725/16	16	65/34	.030	0.76	.122	3.10	4.45
2725/18	18	65/36	.030	0.76	.110	2.80	7.06
2725/20	20	41/36	.030	0.76	.102	2.60	11.2
2725/22	22	26/36	.030	0.76	.094	2.40	18.1
2725/24	24	19/36	.030	0.76	.087	2.20	28.7
2725/26	26	11/36	.030	0.76	.083	2.10	45.8
2725/28	28	7/36	.030	0.76	.079	2.00	72.8

Standard Put-Ups: 100 feet, 500 feet, 1,000 feet

Colors Available: Black, Red, White, Green, Yellow, Blue, Brown, Grey, Violet, Orange