

#DES210 Non-Fray Expandable PET Braided Sleeving – Flame Retardant

Daburn Expandable PET (polyethylene terephthalate) Sleeving is ideal for general all-purpose wire management and bundling in industrial, commercial and home environments. This no fray design is field ready and can be clean cut with scissors.

Description: Expandable monofilament PET braided sleeving that easily expands for ease of installation and then pulls tight for snug fit. Non fray design can be cut with scissors. Hot knife is not required.

- Non-Fray
- Flame Retardant
- Cut and abrasion resistant
- · Resist gasoline and all other common automotive fluids
- UL VW-1 certified

Operating Temperature: -70°C to +125°C

Daburn Item No.	Nom. I.D.	Expansion Range	Wall Thickness	Spool Sizes (feet)
DES210-1/8	1/8"	1/8" — 1/4"	.022"	500, 250, 100
DES210-1/4	1/4"	3/16" – 3/8"	.022"	500, 250, 100
DES210-3/8	3/8"	1/4" - 1/2"	.022"	250, 100
DES210-1/2	1/2"	1/4" - 3/4"	.022"	250, 100
DES210-3/4	3/4"	5/8" - 1"	.022"	250, 100, 50
DES210-1 1/4"	1 1/4"	1" – 1-1/2"	.022"	250, 100, 50

Colors Available: Black with white crisscross lines, White with black crisscross lines