



#SH825 – Vinyl Food-Grade Heat Shrink 2:1

Technical Data

- 2:1 maximum shrink ratio
- Minimum Recommended Shrink Temperature: 100°C (212°F)
- Tensile Strength: 3,000 psi
- Durometer: 85 Durometer Shore A
- Storage: Heat sensitive — Store at 70°F or below

Specifications

- Meets US FDA Title 21 CFR 177 specifications, complying with the United States Food and Drug Administration's stringent requirements for indirect contact with food and beverages in food processing and handling facilities
- Flame retardant — Made from UL 94 compliant materials
- Environmentally friendly and safe — Contains no hazardous materials
- Lead free — RoHS, REACH and Conflict Minerals compliant

Daburn Item Number	Size	Expanded Internal Diameter (min.)		Recovered Internal Diameter (max.)		Recovered Wall Thickness Nominal	
		In.	mm	In.	mm	In.	mm
SH825-5/8	5/8"	0.625	15.88	0.313	7.94	0.033	0.84
SH825-3/4	3/4"	0.75	19.05	0.375	9.53	0.033	0.84
SH825-1	1"	1	25.4	0.5	12.7	0.038	0.97
SH825-1 1/4	1 1/4"	1.25	31.75	0.625	15.88	0.041	1.04
SH825-1 1/2	1 1/2"	1.5	38.1	0.75	19.05	0.043	1.09
SH825-2	2"	2	50.8	1	25.4	0.048	1.22
SH825-2 1/2	2 1/2"	2.5	63.5	1.25	31.75	0.058	1.47
SH825-3	3"	3	76.2	1.5	38.1	0.068	1.73
SH825-4	4"	4	101.6	2	50.8	0.073	1.85

Color: White

Call or e-mail for special sizes.