



## Heyco® Nytye® Heavy Duty and Extra Heavy Duty/HVAC Nylon Cable Ties

PART SPECIFICATIONS				PART NO.		DESCRIPTION	PART DIMENSIONS			
Max. Tensile Strength		Max. Bundle Diameter		Natural	UV Black		A Length		B Width	
Lbs.	N	in.	mm.			in.	mm.	in.	mm.	
<b>Heavy Duty</b>										
120	534	1.30	33,0	<b>13172</b>	<b>13172B</b>	NT-120-059	5.91	150	.30	7,6
		1.97	50,0	<b>13175</b>	<b>13175B</b>	NT-120-078	7.87	200		
		2.48	63,0	<b>13178</b>	<b>13178B</b>	NT-120-098	9.84	250		
		3.23	82,0	<b>13181</b>	<b>13181B</b>	NT-120-118	11.81	300		
		3.54	90,0	<b>13183</b>	<b>13183B</b>	NT-120-137	13.78	350		
		3.98	101,0	<b>13185</b>	<b>13185B</b>	NT-120-149	14.96	380		
4.13	105,0	<b>13186</b>	<b>13186B</b>	NT-120-157	15.75	400				
<b>Extra Heavy Duty/HVAC</b>										
175	778	.39	10,0	<b>13208</b>	<b>13208B</b>	NT-175-255	25.59	650	.35	9,0
				<b>13215</b>	<b>13215B</b>	NT-175-315	31.50	800		
				<b>13217</b>	<b>13217B</b>	NT-175-354	35.43	900		
				<b>13218</b>	<b>13218B</b>	NT-175-393	39.37	1000		
				<b>13220</b>	<b>13220B</b>	NT-175-477	47.76	1213		

Standard colors natural and UV Black. Consult Heyco for heat-stabilized material and colors.



- Smooth, radiused edges ensure that Nytyes won't cut into the cable's insulation—or the installer's hand.
- One-piece design reduces cost and installation time.
- Nytyes feature a bent tip for ease of pickup and insertion around small bundles. V-shaped raised ridges on the tip provide a sure grip.
- Close, evenly spaced teeth permit fine adjustment—from .025" (0,6 mm) on the smallest Nytyes to .063" (1,6 mm) on the largest.
- Compliant with MS3367 and MIL-S-23190E



Material

Certifications

Flammability Rating

Temperature Range

Nylon 6/6



Certified by UL for Compliance with both Canadian and U.S. requirements under File E54523

94V-2

-40°F (-40°C) to 185°F (85°C)

Quick Specs