





## Heyco® Shorty Universal Bushings

Single Locking Step for Panel Thickness up to .062" (1,6 mm)  
Mounting Hole Diameter Range: .500" (12,7 mm) to 1.093" (27,8 mm)

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS					
in.	mm.			Black	Maximum Inside Diameter		A Head Diameter		B Overall Height
				in.	mm.	in.	mm.	in.	mm.
.500	12,7	<b>2858</b>	SUB 500	.31	7,6	.60	15,2	.25	6,4
.625	15,9	<b>2861</b>	SUB 625	.44	11,1	.73	18,5		
.750	19,1	<b>2862</b>	SUB 750	.50	12,7	.86	21,8		
.875	22,2	<b>2863</b>	SUB 875	.56	14,3	.94	23,8		
1.000	25,4	<b>2864</b>	SUB 1000	.75	19,0	1.06	27,0		
1.093	27,8	<b>2158</b>	SUB 1093	.81	20,6	1.16	29,4		

Standard color black. Consult Heyco for white and other colors.





- For use in mounting panels **.062" (1,6 mm) and thinner.**
- Absorb vibration and cushion and insulate cables, tubing, hoses or shafts with limited internal clearance.
- Flexible shutters adjust to accommodate and support any shape from .125" (3,2 mm) to a maximum inside diameter of .812" (20,6 mm).
- Fingertip pressure snap-locks the bushing into its mounting hole.
- **See Quick Specs on 6-11.**

## Heyco® Thick Panel Universal Bushings

Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)  
Mounting Hole Diameter Range: .500" (12,7 mm) to 1.500" (38,1 mm)

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS					
in.	mm.			Black	Maximum Inside Diameter		A Head Diameter		B Overall Height
				in.	mm.	in.	mm.	in.	mm.
.500	12,7	<b>3001</b>	UBT 500	.31	7,6	.60	15,2	.55	13,8
.625	15,9	<b>3118</b>	UBT 625*	.44	11,1	.73	18,5	.51	13,0
.750	19,1	<b>3119</b>	UBT 750*	.50	12,7	.84	21,4	.55	13,8
.875	22,2	<b>3120</b>	UBT 875	.56	14,3	.94	23,8		
1.000	25,4	<b>3121</b>	UBT 1000	.75	19,1	1.06	27,0		
1.093	27,8	<b>3002</b>	UBT 1093	.81	20,6	1.16	29,5		
1.375	34,9	<b>3003</b>	UBT 1375	1.00	25,4	1.49	37,8	.56	14,2
1.500	38,1	<b>3122</b>	UBT 1500	1.06	26,9	1.61	40,9		

Standard color black. Consult Heyco for white and other colors.  
\*Single Locking Step for Panel Thickness up to .250" (6,4 mm).



- For use in mounting panels up to **.250" thick.**
- Flexible shutters to absorb vibration on the inside diameter.
- Insulate and mechanically protect electrical and telecommunications cables, tubing, hose, rope, and utility lines.
- Withstand a push back force of 35 pounds.
- Locking fingers snap into holes with fingertip pressure.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Available in multiple sizes for use in .500" (12,7 mm) to 1.500" (38,1 mm) diameter holes.
- **See Quick Specs on 6-11.**