

“Stay Connected” with



HEYware Products

a PennEngineering® Company






- Quick, easy installation is fast, saving time and money.
- Wide cable diameter range handles multiple applications.
- Material choices cover a number of application requirements for flammability and temperature.
- Releasable and reusable.
- Secure clamping will not release easily.
- Locking feature prevents twisting apart.




Heyco® Speed Bundle Clamps

BUNDLE DIAMETER				PART NO.			DESCRIPTION	PART DIMENSIONS						MOUNTING HOLE DIAMETER			
A		Natural	HS/UV Black	V-0 Black	Overall Height (closed)			Width		Depth		D		in.	mm.		
Minimum	Maximum				in.	mm.	B	mm.	C	mm.	D	in.	mm.				
.29	7,4	.44	11,2	15250	15250B	15250F	SBC 437	.78	19,8	1.12	28,4			-	-		
.41	10,4	.69	17,5	15254	15254B	15254F	SBC 687	.97	21,8	1.24	31,5	.31	7,9	-	-		
.60	15,2	.88	22,2	15258	15258B	15258F	SBC 875	1.27	32,3	1.66	42,2			-	-		
.87	22,1	1.09	27,8	15260	15260B	15260F	SBC 1093	1.64	41,7	2.29	58,2			-	-		
1.10	27,9	1.50	38,1	15264	15264B	15264F	SBC 1500	2.25	57,2	3.05	77,5	.50	12,7	-	-		
1.37	34,5	2.00	50,8	15268	15268B	15268F	SBC 2000	2.50	63,5	3.46	87,6			-	-		
Push Mount																	
.29	7,4	.44	11,2	15360	15360B	15360F	SBCPM 437-187	.92	23,4	1.12	28,4					.187	4,8
				15390	15390B	15390F	SBCPM 437-250									.250	6,4
.41	10,4	.69	17,5	15364	15364B	15364F	SBCPM 687-187	1.05	26,7	1.24	31,5	.31	7,9			.187	4,8
				15394	15394B	15394F	SBCPM 687-250									.250	6,4
.60	15,2	.88	22,2	15368	15368B	15368F	SBCPM 875-187	1.40	35,6	1.66	42,2					.187	4,8
				15398	15398B	15398F	SBCPM 875-250									.250	6,4

SBC



SBCPM



PANEL THICKNESS Min. .031 (0,8 mm)
Max. .093 (2,4 mm)

Quick Specs

Material – Flammability Rating

Natural Nylon 6/6 – UL 94 V-2

Black Heat Stable / UV Stable Nylon – UL 94 V-2

Black Nylon 6/6 – UL 94 V-0

Temperature Range

32°F (0°C) to 185°F (85°C)

-40°F (-40°C) to 239°F (115°C)

-40°F (-40°C) to 185°F (85°C)