

MCV (M23) Series Field Wireable Plugs

12 & 19 Conductor M23 Series Field Wireable Plugs, 18-24AWG



Male Field Wireable Plugs | Solder Cups/Crimp Pins | 300/150V, 8A Max | IP67 Rating





| # of | Male Faceview | Rating | Wire AWG | Cable O.D. Range | Contact Type | Part Number | |
|-------|--|----------------|-------------|---------------------|-----------------|----------------|-----------------|
| Poles | | | | | | Female Threads | Male Threads |
| 12 | 0 9 1 0 0 0 7 12 10 2 0 0 0 0 | 300V 8A MAX | 18-24 AWG | 5-13 mm | Solder Cup | MCV-12MP-FW-SC | MCV-12MPM-FW-SC |
| | 60 0 03 50 04 M23 x 1 | | | | Crimp Pin | MCV-12MP-FW-CC | MCV-12MPM-FW-CC |
| 19 | | 150V 8A MAX | 18-24 AWG | 5-13 mm | Solder Cup | MCV-19MP-FW-SC | MCV-19MPM-FW-SC |
| | M23 x 1 | | | | Crimp Pin | MCV-19MP-FW-CC | MCV-19MPM-FW-CC |

Connection via solder cup terminal or crimp pin. Voltage and amperage ratings are cable dependent and are based on 600V 18 AWG cable. Cables with lower voltage ratings or smaller wire gauge will lower these ratings.

Specifications:

Body: Nickel Plated Brass

Contacts: Copper Alloy with Gold Plating

O-Ring: NBR Insert: PBT

Connections: Crimp/Solder

Temperature: -40° C to $+105^{\circ}$ C (-40° F to $+221^{\circ}$ F)





Male Plug with Female Threads

Male Plug with Male Threads

| # of Poles | Crimp Pin | Wire AWG | Male Contacts | | | |
|------------|--------------|---------------------------|----------------|----------|-------------------|--|
| # UI FUICS | Offilip Fili | Wife AWG | Stamped Reel | Stamped | Machined | |
| 12 | 0 | 18-20 AWG | DBMCP-CF-18 | DBMCP-18 | MCV-PIN-C-18 | |
| _ | | 22-24 AWG | DBMCP-CF DBMCP | | MCV-PIN-C | |
| 19 | | 18 AWG | N/A | N/A | MCV19-1.5PIN-18 | |
| | | 20-24 AWG | N/A | N/A | MCV19-1.0PIN-20 | |
| | | 18 AWG Male Ground Pin | N/A | N/A | MCV19-1.5PIN-18-G | |

| # of Poles | Removal Tool | Crimp Tools for I | Machined Pins | Assembly Tool for | |
|------------|--------------|-------------------|---------------|----------------------------|--|
| # 01 F0165 | Removal 1001 | Locator Tool | Crimp Tool | Female Threaded Connectors | |
| 12 | MCV12ES | MCTP-V12 | CCPZ-MIL | MCV-001 | |
| 19 | MCV19ES | MCTP-V19 | CGPZ-IVIIL | | |

Crimp Tool and Crimp Tool Locator are ordered separately. Locators fit into crimp tool and are necessary for proper crimping.