



# MIL-SPEC Series Field Wireable Plugs


2 & 3 Conductor 5015 Industrial Equiv. Field Wireable Plugs, 16-18AWG



Field Wireable Plugs | Size 10SL | 600 Volt, 13 amps MAX | IP67 Rating



F  
MIL-SPEC

| # of Poles | Male Faceview                                                                                                | Rating              | Wire AWG  | Cable O.D. Range | Male Plugs         | Female Plugs       |
|------------|--------------------------------------------------------------------------------------------------------------|---------------------|-----------|------------------|--------------------|--------------------|
| 2          | <br>10SL-2<br>0.6250"-24NEF | 600V Max<br>13A Max | 16-18 AWG | 3-9 mm           | MS10SL-2MP-FW16-SC | MS10SL-2FP-FW16-SC |
| 3          | <br>10SL-3<br>0.6250"-24NEF | 600V Max<br>13A Max | 16-18 AWG | 3-9 mm           | MS10SL-3MP-FW16-SC | MS10SL-3FP-FW16-SC |

Voltage and Amperage ratings are cable dependent and are based on 600V 16AWG Cable.  
Termination made by solder cup.

Specifications:

- Body: Nickel Plated Brass
- Contacts: Copper Alloy with Silver Plating
- Cable Seal: CR/NBR & TPE
- Coupling Nut: Nickel Plated Brass
- Insert: PBT
- Connections: Solder Cup Terminals
- Temperature: -40 °C to +105°C (-40°F to +194°F)

