



MIL-SPEC Series Receptacles

2, 3, 5 & 7 Conductor 5015 Industrial Equiv. Receptacles



Panel Mount Receptacles | Size 16S | Solder Cup | IP67 Rating

# of Poles	Male Faceview	Rating	Wire AWG	Male Receptacles	Female Receptacles
2	 16S-2 1.000"-20UNEF	600V Max 13A Max	16-18 AWG	MS16S-2MR-PM-SC	MS16S-3FR-PM-SC
3	 16S-3A 1.000"-20UNEF	600V Max 13A Max	16-18 AWG	MS16S-3AMR-PM-SC	MS16S-3AFR-PM-SC
	 16S-3B 1.000"-20UNEF	600V Max 13A Max	16-18 AWG	MS16S-3BMR-PM-SC	MS16S-3BFR-PM-SC
5	 16S-5 1.000"-20UNEF	600V Max 8A Max	16-18 AWG	MS16S-5MR-PM-SC	MS16S-5FR-PM-SC
7	 16S-7 1.000"-20UNEF	600V Max 5A Max	16-18 AWG	MS16S-7MR-PM-SC	MS16S-7FR-PM-SC

F
MIL-SPEC

Voltage and Amperage ratings are cable dependent and are based on 600V 16AWG Cable.

Termination made by solder cup.

Specifications:

Shell: Nickel Plated Zinc Diecast
Insulator: PBT
Contacts: Copper Alloy with Silver Plating
Gasket: NBR
Insert: PBT
Temperature: -40°C to +105°C (-40°F to +221°F)

