



MDC (M12) Series Receptacles

6, 8 10 & 12 Conductor MDC Series Receptacles



Solder Cup Receptacles | 1/2"-14 NPT & Metric Threads | 60V, 2A | IP69 Rating




# of Poles	Male Faceview	Rating	Wire AWG	1/2" - 14 NPT Threads		M20 x 1.5 Threads	
				Male Receptacles	Female Receptacles	Male Receptacles	Female Receptacles
6	 M12 x 1	60V 2A MAX	24 AWG MAX	MDC-6MR-2-SC	MDC-6FR-2-SC	MDC-6MR-M20-SC	MDC-6FR-M20-SC
8	 M12 x 1	60V 2A MAX	24 AWG MAX	MDC-8MR-2-SC	MDC-8FR-2-SC	MDC-8MR-M20-SC	MDC-8FR-M20-SC


Other mounting threads are available, please consult the factory.

Stainless Steel is available for the 1/2" NPT version, add a "-SS" suffix (e.g. MDC-8MR-2-SC becomes MDC-8MR-2-SC-SS).

1/2"-14NPT Threads




Male Receptacles




Female Receptacles

M20 Threads



Male Receptacles



Female Receptacles

Specifications:

Shell: 1/2"-14NPT: Clear Anodized Aluminum

M20 x 1.5: Nickel Plated Brass

Insulator: Polyamide

Contacts: Copper Alloy with Gold Plating

Lock Nut:

Zinc Plated Steel

Jam Nut:

Nickel Plated Brass

O-Ring:

NBR

Temperature:

-40°C to 105°C (-40°F to +221°F)