




Profibus-PA Series Field Wireable Plugs

4 Conductor Profibus-DP Series Field Wireable Plugs




Field Wireable Plugs | 600 Volt, 15 amps MAX | 250 Volt, 4 amps MAX | IP67 Rating




7/8"-16UN Field Wireable Plugs						
# of Poles	Male Faceview	Rating	Wire AWG	Cable O.D. Range	Part Number	
					Male Plugs	Female Plugs
4	 7/8"-16UN2	600V 15A MAX	14-22 AWG	5-13 mm	PBIN-4MPM-FW-SS	PBIN-4FP-FW-SS
				8-17 mm	PBIN-4MPM-FWX-SS	PBIN-4FP-FWX-SS


Connection via screw terminal. Voltage and amperage ratings are cable dependent and are based on 600V 14 AWG cable. Cables with lower voltage ratings or smaller wire gauge will lower these ratings.




Male Staright with Male Threads




Female Staright with Female Threads

M12 Field Wireable Plugs						
# of Poles	Male Faceview	Rating	Wire AWG	Cable O.D. Range	Part Number	
					Male Plugs	Female Plugs
4	 M12 x 1	250V 4A MAX	18-24 AWG	3-6.5 mm	PBDC-4MP-FW07-SS	PBDC-4FP-FW07-SS
				4-8 mm	PBDC-4MP-FW09-SS	PBDC-4FP-FW09-SS
				8-10 mm	PBDC-4MP-FW11-SS	PBDC-4FP-FW11-SS

Connection via screw terminal. Voltage and amperage ratings are cable dependent and are based on 600V 14 AWG cable. Cables with lower voltage ratings or smaller wire gauge will lower these ratings.



Male Straight with Male Threads



Female Straight with Female Threads

Specifications:

Body: Polyamide
Contacts: Copper Alloy with Gold Plating
Coupling Nut: Stainless Steel
O-Ring: NBR

Insert: PVC
Connections: Screw Terminals
Temperature: -40°C to +90°C (-40°F to +194°F)