



PRINTED LEGEND: cULus AWM STYLE 20233 80°C 300V - AWM I/II A/B 80°C 300V FT1
- ETHERNET CABLE CAT 5E - (4x2xAWG24)H2/H - (Week/Year) - CE

B	SPECIFICATIONS:	
	UL STYLE:	AWM 20233
	CSA STYLE:	I / II AB
	CABLE JACKET MATERIAL:	Teal PUR
	COND. JACKET MATERIAL:	Polyolefin
	CONDUCTOR:	24AWG - Stranded
	PAIRING:	Blu x Wht/Blu, Org x Wht/Org, Grn x Wht/Grn, Brn x Wht/Brn
	RoHS?:	Yes
	ELECTRICAL REQUIREMENTS:	
	CAT 5e	
A	MECHANICAL REQUIREMENTS:	
	EXTRUSION STYLE:	PRESSURE EXTRUSION
	TEMPERATURE:	-40°C - +80°C (static, dynamic & storage)
	BEND RADIUS (STATIC):	5x O.D.
	BEND RADIUS (DYNAMIC):	7.5x O.D.
	FLEX LIFE:	6MM cycles
	CHAIN LENGTH:	15m (only horizontal)
	MAX SPEED:	300m/min
	MAX ACCELERATION:	50m/s²

TABLE A	
P/N	LENGTH
60GP001-250	250' [76m]
60GP001-500	500' [152m]
60GP001-1000	1000' [305m]

Cable supplied on a single spool.
1 break allowed for lengths
of 1000' or more with no
piece being shorter than 250'

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	
	DRAWN DATE	02/12/2021
	CHECKED BY	GO
	CHECK DATE	02/12/2021
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION		
TITLE:		
24/8 TEAL PUR CABLE		
SIZE	DWG. NO.	REV
B	60GP001-ZZ	A
SCALE: 3:1	WEIGHT:	SHEET 1 OF 1