



| Construction / Specifications | |
|-------------------------------|---|
| Wire: | - 4x2x24AWG Stranded Tinned Copper |
| | - Polyolefin Insulation, Nom OD 1.15mm |
| Shield: | - Tinned Copper Braid Shield 70% min coverage |
| | - Aluminum Mylar Shield |
| Jacket: | - Teal PVC |
| Resistance: | <89 Ω /m |
| Working Voltage: | 600V |
| Nom. Capacitance: | 49pF/m |
| Impedance @ 1-100MHz | 100 +/- 15 Ω |
| Temperature Range: | -20°C to +80°C |

| TABLE A | |
|--------------|--------------|
| PART NUMBER | LENGTH |
| 60GS001-0250 | 250' [76m] |
| 60GS001-0500 | 500' [152m] |
| 60GS001-1000 | 1000' [305m] |

Cable supplied on a single spool.
1 break allowed for lengths
of 1000' or more with no
piece being shorter than 250'

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

| | | |
|---|------------|------------|
| UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM] | DRAWN BY | ADM |
| | DRAWN DATE | 12/19/2017 |
| | CHECKED BY | |
| | CHECK DATE | |
| | | |
| MATERIAL | COMMENTS: | |
| FINISH | | |
| DO NOT SCALE DRAWING | | |

| MENCOM CORPORATION | | | |
|------------------------------------|------------|--|--------------|
| TITLE: | | | |
| 4 PR. INDUSTRIAL ETHERNET CABLE | | | |
| SIZE | DWG. NO. | | REV |
| B | 60GS001-ZZ | | A |
| SCALE: 5:1 | WEIGHT: | | SHEET 1 OF 1 |