



Technical data	
Current	10 A (A.C. and D.C.)
Voltage	400 V
Rated impulse withstand voltage	6kV
Pollution degree	3
Wire cross-section	0,14 mm <sup>2</sup> - 2,50 mm <sup>2</sup>
AWG size	26 - 14
Operating temperature range (min, max)	(-40°C ... +125°C)
Contact type	silver plated
Mating cycles	≥ 500
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure
PE wire cross-section	0,50 - 4 mm <sup>2</sup> ; AWG 20 - 12
Insulation resistance	≥ 10 GΩ
Weight	127,67 g

Description:						
Female insert, 42 poles + ground, Spring connection contacts SQUICH, 10A, 400V, silver plated,						
Approvals / Standards						
Reference standard			EN 61984:2009-06			
Quality mark			EAC			
Conformity			CQC, CE			
UNLESS OTHERWISE SPECIFIED:		DRAWN BY	DCG	MENCOM CORPORATION		
DIMENSIONS ARE IN MM TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 3° BEND ± 5° ONE PLACE DECIMAL ±.2 TWO PLACE DECIMAL ±.1	DRAWN DATE	08/20/2021	TITLE:  42 PL FEM INSERT; 400V 10A SLVR PLT			
	CHECKED BY	JJH				
	CHECK DATE	08/20/2021				
MATERIAL		COMMENTS:		SIZE <b>B</b>	DWG. NO.  CDSHF-42	REV <b>A</b>
FINISH						
DO NOT SCALE DRAWING						
		SCALE: 3:2		WEIGHT:		SHEET 1 OF 1

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.