



MATERIALS	
HOUSING:	GLASS REINFORCED THERMOPLASTIC
SCREWS:	NICKEL PLATED BRASS HARDWARE
	NICKEL PLATED BRASS
RATINGS:	UL - 600V, 16A. EN 500V/6kV/3, 16A
WIRE AWG	12 - 20AWG [4 - 0.5 sqmm]
STRIP LENGTH	7 MM
SCREW TORQUE	0.5 Nm (4.4 LB.IN.)
APPROVALS:	UL & CSA

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	ADM	MENCOM CORPORATION TITLE: 6 POL MAL INSERT		
	DRAWN DATE	09/22/2016			
	CHECKED BY				
	CHECK DATE				
MATERIAL	COMMENTS:		SIZE	DWG. NO.	REV
FINISH			B	CNEM-06T	A
DO NOT SCALE DRAWING			SCALE: 1:1	WEIGHT:	SHEET 1 OF 1