



MATERIALS	
HOUSING:	GLASS REINFORCED THERMOPLASTIC
	NICKEL PLATED BRASS HARDWARE
SCREWS:	NICKEL PLATED BRASS
	M4 SCREW
CONTACTS:	SILVER PLATED COPPER ALLOY
WIRE GAUGE:	16-10 AWG
RATINGS:	UL - 600V, 35A max. EN 400/690V/6kV/3, 35A
TIGHTENING TORQUE:	1.2Nm (10.6 lb.in)
APPROVALS:	UL, CSA, & CCC

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.



UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	ADM	MENCOM CORPORATION			
	DRAWN DATE	09/22/2016	TITLE: 6 PL FEM SCREW INSERT 35AMP			
	CHECKED BY					
	CHECK DATE					
MATERIAL	COMMENTS:		SIZE	DWG. NO.	REV	
FINISH			B	CPF-06	A	
DO NOT SCALE DRAWING			SCALE: 1:1	WEIGHT:	SHEET 1 OF 1	