



For use with CCMA-x.x or CCMD-x.x contacts.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	DRAWN IN SW	12/20/2013	JJH

MATERIALS			
HOUSING:		GLASS REINFORCED THERMOPLASTIC UL 94 V0	
RATINGS:		UL - 600V, 16A. EN 500V/6kV/3, 16A	
WIRE AWG		12 - 26AWG [4 - 0.14 sqmm]	
TEMP:		-40°C to +125°C	
APPROVALS:		UL & CSA	
UNLESS OTHERWISE SPECIFIED:		NAME	MENCOM CORPORATION
DIMENSIONS ARE IN INCHES		DRAWN	
TOLERANCES:		RSC	
FRACTIONAL ±1/64		CHECKED	
ANGULAR: MACH ±5° BEND ±5°		ENG APPR.	
TWO PLACE DECIMAL ±.01		MFG APPR.	8 PL MALE INSERT
THREE PLACE DECIMAL ±.004		Q.A.	
		COMMENTS:	
MATERIAL		SIZE	DWG. NO. CQM-08
FINISH		REV	
DO NOT SCALE DRAWING		SCALE: 3:2	SHEET 1 OF 1
		WEIGHT:	