

D

D

—PG13.5  
FEMALE  
THREADED  
OPENING

A technical drawing of a rectangular component. The top part is a dark grey rectangle with a smaller dark grey rectangle centered above it. The bottom part is a dark grey rectangle with a central horizontal slot. The width of the bottom part is indicated by a dimension line with arrows at the bottom, labeled [63] 2.48. To the left of the component, a dimension line with arrows indicates a height of [62] 2.44. A vertical line with arrows at the top and bottom indicates a height of [62].

A technical drawing of a cylindrical component. The top section features a flange with a central circular hole. The label 'G' is positioned to the right of the flange. The bottom section is a plain cylinder. Two horizontal arrows at the bottom point to the text '29.4' and '116' respectively.

SEAL RATING OF IP 65, UL TYPE 4, 4X OR 12 ONLY  
ACHIEVED WHEN FULLY LATCHED TO MATING BASE  
AND WITH AN APPROPRIATE SEALING GLAND INSTALLED

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	DRAWN BY	ADM
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	09/22/2016
	CHECKED BY	
	CHECK DATE	
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

HOUSING MATERIALS	
BODY:	EPOXY COATED DIE CAST ALUMINUM

MENCOM CORPORATION		
TITLE:		
CZ 15 PL TE HD		
SIZE <b>B</b>	DWG. NO. CZV-15L	REV <b>A</b>
		SCALE: 1:1
WEIGHT:	SHEET 1 OF 1	