



OPERATING TEMPERATURE RANGE OF -40C TO 125C

SEAL RATING OF IP 66, UL TYPE 4, 4X OR 12 ONLY  
ACHIEVED WHEN FULLY LATCHED TO MATING BASE  
AND WITH AN APPROPRIATE SEALING GLAND INSTALLED

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.

HOUSING MATERIALS				
LEVER:	THERMOPLASTIC ELASTOMER & STAINLESS STEEL			
BODY:	THERMOPLASTIC ELASTOMER			
ADAPTER:	NICKEL PLATED BRASS			
O-RING:	BUNA-N			
UNLESS OTHERWISE SPECIFIED:  DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	DCG	MENCOM CORPORATION  TITLE:  15 PL TE HD 1LVR 1/2" NPT	
	DRAWN DATE	01/28/2022		
	CHECKED BY	JJH		
	CHECK DATE	01/28/2022		
	COMMENTS:		SIZE <b>B</b>	
MATERIAL			DWG. NO.	
FINISH			CZVT-15.4LG	
			REV <b>A</b>	
DO NOT SCALE DRAWING			SCALE: 1:1	SHEET 1 OF 1