



В

А

		HOUSING MATERIALS				
	BODY:		ATED DIE CAST	AMPS:		
		ALUMINUM			NEMA/UL	
	GASKET:	: POLYAMIDE		R MOUNTING MOUNTING INCOMING F		
	HANDLE:					
	LEVERS:	STAINLESS				
OPERATING TEMPER	ATURE: (-10	°C / +60° C ((+14° F / +140° F))	WIRE S		
MOUNTING KIT ORDERED			UNLESS OTHERWISE SPECIFIED:	DRAWN BY	[
SEPARATELY CONTAINS	DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	10/			
M4x0.7 SS SCREW, NYLC		CHECKED BY				
SPLIT LOCKWASHER AN		CHECK DATE	10/			
P/N: D-PIC-MT						
			_			
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS			MATERIAL	COMMENTS:		
			FINISH			
PROHIBITED.			DO NOT SCALE DRAWING			
5	4		3			

250 VAC MAX. <> <> <> 수 Ô Ο \circ 0 $\overline{}$ 0 Ð

1

2

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

В

С

D

					.					
	PIC R	ATING	S/SP	ECIFICAT	ONS					
			250V							
			3A							
L EN 60529:			4, 4X, 12 IP65							
NG SCREW SIZE:			M4 (8-32) (304 or 316SS for 4X)							
NG SCREW TORQUE:			1.2~1.8N-m (0.9~1.3 Lb-Ft)							
NG POWER WIRE SIZE:				0.5 ~ 4.0 sq mm / 20-12AWG						
				10 ~ 11 mm						
DCG										
	Ν	MENCOM CORPORATION								
10/19/202										
JJH	TITLE:									
10/19/202	23	. – –						A		
		ARG 10A RCPT;RJ45;USB AA;3A;32								
	0.75									
		SIZE DWG. NO. REV								
	B	B DAR-RJ45-USB-AFAF-R-32								
	SCALE	: 2:3	WEI	GHT:		SHEET	1 OF 1			
								1		

1