


These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

	HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS					
BODY:	EPOXY COATED DIE CAST ALUMINUM		NEMA/UL EN 60529:			4, 4X, 12 IP65		
GASKET:	THERMOPLASTIC ELASTOMER		MOUNTING SCREW SIZE:			M4 (8-32) (304 or 316SS for 4X)		
HANDLE:	POLYAMIDE		MOUNTING SCREW TORQUE:			1.2~1.8N-m (0.9~1.3 Lb-Ft)		
LEVERS:	STAINLESS STEEL							
			UNLESS OTHERWISE SPECIFIED:		<div>MENCOM CORPORATION</div> <div>TITLE: 9 PIN D-SUB; 06</div>			
			DIMENSIONS ARE IN INCHES AND [MM]					
			DRAWN BY DCG					
			DRAWN DATE 06/25/2018					
			CHECKED BY JJH					
			CHECK DATE 06/25/2018		<div>SIZE DWG. NO. REV</div> <div>B DB09-06LS C</div> <div>SCALE: 1:1 WEIGHT: SHEET 1 OF 1</div>			
			COMMENTS:					
			MATERIAL					
			FINISH					
			DO NOT SCALE DRAWING					

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
ALL D-SUBS	FEMALE	MALE

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.