


STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 5e JACK	CAT 5e JACK
ALL D-SUBS	FEMALE	MALE

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT



HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS				
BODY:	EPOXY COATED DIE CAST ALUMINUM	NEMA/UL EN 60529:		4, 4X, 12 IP65		
GASKET:	THERMOPLASTIC ELASTOMER	MOUNTING SCREW SIZE:		M4 (8-32) (304 or 316SS for 4X)		
HANDLE:	POLYAMIDE	MOUNTING SCREW TORQUE:		1.2~1.8N-m (0.9~1.3 Lb-Ft)		
LEVERS:	STAINLESS STEEL					
		UNLESS OTHERWISE SPECIFIED:		MENCOM CORPORATION		
		DIMENSIONS ARE IN INCHES AND [MM]				
		DRAWN BY	DCG			
		DRAWN DATE	12/04/2017			
		CHECKED BY	JJH			
		CHECK DATE	12/04/2017	TITLE: DB9 X 2; 4 RJ45; 32		
		COMMENTS:		SIZE DWG. NO. REV		
				B DB09-2-4RJ45-32LS C		
				SCALE: 2:3	WEIGHT:	SHEET 1 OF 1
		DO NOT SCALE DRAWING				