


NOTE: RJ11 JACK IS TECHNICALLY AN RJ12 JACK IN THAT IT HAS ALL 6 CONTACTS. IT IS SUITABLE FOR USE WITH ALL RJ11 AND RJ12 APPLICATIONS.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ11	JACK	JACK
ALL D-SUBS	FEMALE	MALE

MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS	
BODY:	EPOXY COATED DIE CAST ALUMINUM		
GASKET:	THERMOPLASTIC ELASTOMER	NEMA/UL EN 60529:	4, 4X, 12 IP65
HANDLE:	POLYAMIDE	MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
LEVERS:	STAINLESS STEEL	MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)
 UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]		DRAWN BY	ADM
		DRAWN DATE	07/02/2021
		CHECKED BY	DCG
		CHECK DATE	07/02/2021
		MATERIAL	
		FINISH	
		DO NOT SCALE DRAWING	
		COMMENTS:	
		MENCOM CORPORATION	
		TITLE: 2 DB09;RJ11;CX;24	
		SIZE B	DWG. NO. DB09-2-RJ11-CX-24LS
		SCALE: 7:8	REV C
		WEIGHT:	SHEET 1 OF 1