



INTERIOR

CAT 6 JACK

**EXTERIOR** 

CAT 6 JACK

CONN. TYPE

RJ45

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

	BODY:	EPOXY COATED DIE CAST ALUMINUM									
				PIC RATINGS/SPECIFICATIONS							
	GASKET:	THERMOPL	LASTIC ELASTOMER								
	HANDLE:	POLYAMIDE STAINLESS STEEL		NEMA/UL   EN 60529: MOUNTING SCREW SIZE:			4, 4X, 12   IP65 M4 (8-32) (304 or 316SS for 4X)				
	LEVERS:										
OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +14				MOUNT	ING SCRE	EW TORQUE: 1.2~1.8N-m (0.9~1.3 Lb-Ft)					
MOUNTING KIT ORDERE	D		UNLESS OTHERWISE SPECIFIED:	DRAWN BY	ADM	١ ٨ ٨	AACNICONA CODDODATIONI				
SEPARATELY CONTAINS  M4x0.7 SS SCREW, NYLON WASHER,  SPLIT LOCKWASHER AND M4 NUT  LISTED ENCLACE			US DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	07/16/2021	MENCOM CORPORATION					
				CHECKED BY	APR	TITLE: DB09F;RJ45;USB-AA;16					
				CHECK DATE	07/16/2021						
P/N: D-PIC-MT		- Conta									
PROPRIETARY AND CONFIDENTIAL				COMMENTS							
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS			MATERIAL								
			FINISH				B DB09F-RJ45-USB-AFAF-16 B				
							:16 WE				

HOUSING MATERIALS