



HOUSING MATERIALS		These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.									
BODY:	EPOXY COATED DIE CAST ALUMINUM	PIC RATINGS/SPECIFICATIONS									
GASKET:	THERMOPLASTIC ELASTOMER	NEMA/UL EN 60529:		4, 4X, 12 IP65							
HANDLE:	POLYAMIDE	MOUNTING SCREW SIZE:		M4 (8-32) (304 or 316SS for 4X)							
LEVERS:	STAINLESS STEEL	MOUNTING SCREW TORQUE:		1.2~1.8N-m (0.9~1.3 Lb-Ft)							
OPERATING TEMPERATURE: (-25°C / +85° C (+13° F / +185° F))											
<div>MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT</div> <div>P/N: D-PIC-MT</div> <div><div>PROPRIETARY AND CONFIDENTIAL</div><div>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.</div></div> <div><div><div><div><div></div><div>UL</div><div>us</div></div><div><div>LISTED</div><div>ENCL. ACC.</div><div>5JR2</div></div></div></div></div>		UNLESS OTHERWISE SPECIFIED:		DRAWN BY		ADM		<div>MENCOM CORPORATION</div> <div>TITLE:</div> <div>DB9; 6M; 16</div>			
		DIMENSIONS ARE IN INCHES AND [MM]		DRAWN DATE		07/14/2021					
				CHECKED BY		DCG					
				CHECK DATE		07/16/2021					
		MATERIAL		COMMENTS:							
		FINISH				SIZE		DWG. NO.		REV	
						B		DB09M-6M-16LS		B	
		DO NOT SCALE DRAWING				SCALE: 13:16		WEIGHT:		SHEET 1 OF 1	

5

4

3

2

1