


STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
ALL D-SUBS	FEMALE	MALE
BNC	JACK	JACK

MOUNTING KIT ORDERED SEPARATELY CONTAINS M6x1 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M6 NUT
P/N: D-PIC48-MT

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS						
BODY:	EPOXY COATED DIE CAST ALUMINUM	NEMA/UL EN 60529:		4, 4X, 12 IP65				
GASKET:	THERMOPLASTIC ELASTOMER	MOUNTING SCREW SIZE:		M6 (1/4-20) (304 or 316SS for 4X)				
HANDLE:	STAINLESS STEEL	MOUNTING SCREW TORQUE:		3.0~3.6N-m (2.2~2.7 Lb-Ft)				
DRAWN BY: CHECKED BY: CHECK DATE: COMMENTS:		UNLESS OTHERWISE SPECIFIED:		MENCOM CORPORATION TITLE: DB25 X 2; 4 X BNC; 48				
		DIMENSIONS ARE IN INCHES AND [MM]						
	MATERIAL		SIZE		DWG. NO.		REV	
	FINISH		B		DB25-2-4BNC-48		B	
DO NOT SCALE DRAWING		SCALE: 2:3		WEIGHT:		SHEET 1 OF 1		