



Technical drawing of a rectangular plate with the following dimensions and features:

- Overall width: $[88]$ 3.46
- Overall height: $[110]$ 4.33
- Inner rectangle width: $[76]$ 2.99
- Inner rectangle height: $[65]$ 2.56
- Four holes, each with a diameter of $\phi .18$ and a depth of $4X$.
- The holes are located at the corners of the inner rectangle.

UL
LISTED
ENCL. ACC.
5JR2

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
AND [MM]

PIC RATINGS/SPECIFICATIONS	
VOLTS:	250V
AMPS:	3A
SCCR:	0.2kA
NEMA/UL EN 60529:	4, 4X, 12 IP65
MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)
INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
WIRE STRIP LENGTH:	10 ~ 11 mm

ED:	DRAWN BY	DCG
	DRAWN DATE	10/21/2020
	CHECKED BY	
	CHECK DATE	

TITLE: IEC RCPT; RJ45; 3A; 32

SIZE B	DWG. NO. DEC-RJ45-R-32	REV B
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1

CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

MATERIAL
FINISH
DO NOT SCALE DRAWING