

2

56

2.2 PLUGGABLE TERMINAL BLOCK SCREW CONNECTIONS

D

С

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

## PIC RATINGS/SPECIFICATIONS

		125V		
		15A		
		10kA		
JL   EN 60529:		4, 4X, 12   IP65		
NG SCREW SIZE:		M4 (8-32) (304 or 316SS for 4X)		
NG SCREW TORQUE:		1.2~1.8N-m (0.9~1.3 Lb-Ft)		
NG POWER WIRE SIZE:		0.5 ~ 4.0 sq mm / 20-12AWG		
TRIP LENGTH:		10 ~ 11 mm		
DCG				
06/14/2019	MENCOM CORPORATION			
	TITLE:			
			. 57 1/	А
	SIMPLX; 9 PIN D BL-HO; SZ 16			
:				
	SIZE DWG. NO. REV <b>R</b> DHDP1-DB9-16LS <b>R</b>			
	<b>B</b> D	HDF1-DB9-16L3	B	
	SCALE: 1:1 W	EIGHT:	SHEET 1 OF 1	
	2		1	