



These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS	
BODY:	EPOXY COATED DIE CAST ALUMINUM	VOLTS:	125V
GASKET:	THERMOPLASTIC ELASTOMER	AMPS:	3A
HANDLE:	POLYAMIDE	SCCR:	0.2kA
LEVERS:	STAINLESS STEEL	NEMA/UL   EN 60529:	4, 4X, 12   IP65
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]		MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
		MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)
		INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
		WIRE STRIP LENGTH:	10 ~ 11 mm
MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT P/N: D-PIC-MT		DRAWN BY	DCG
		DRAWN DATE	11/26/2018
		CHECKED BY	GO
		CHECK DATE	11/26/2018
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.		MENCOM CORPORATION	
		TITLE: GFI; D-HWY 9 PIN; RJ; 3A	
		SIZE	DWG. NO.
		B	DHGF-DB9-RJ45-R-32
DO NOT SCALE DRAWING		SCALE: 2:3	WEIGHT:
		SHEET 1 OF 1	
		REV	
		E	