



SOUTH AFRICA / INDIA 16 AMPERE-250 VOLT TYPE M OUTLET, 6 AMPERE-250 VOLT TYPE D OUTLET, 45mmX45mm MODULAR SIZE, SHUTTERED CONTACTS, 2 POLE-3 WIRE GROUNDING [2P+E].

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

<div>HOUSING MATERIALS</div> <div><div>BODY:</div><div>EPOXY COATED DIE CAST ALUMINUM</div></div> <div><div>GASKET:</div><div>THERMOPLASTIC ELASTOMER</div></div> <div><div>HANDLE:</div><div>POLYAMIDE</div></div> <div><div>LEVERS:</div><div>STAINLESS STEEL</div></div>			PIC RATINGS/SPECIFICATIONS				
			VOLTS:		250V		
			AMPS:		6A / 15A		
			SCCR:		0.2kA		
			NEMA/UL EN 60529:		4, 4X, 12 IP65		
OPERATING TEMPERATURE: (-5°C / +50° C (+23° F / +122° F))			MOUNTING SCREW SIZE:		M5 (10-32) (304 or 316SS for 4X)		
			MOUNTING SCREW TORQUE:		1.2~1.8N-m (0.9~1.3 Lb-Ft)		
<div>MOUNTING KIT ORDERED SEPARATELY CONTAINS M5x0.8 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M5 NUT</div> <div>P/N: D-PIC-MT-M5</div>			UNLESS OTHERWISE SPECIFIED:		<div>MENCOM CORPORATION</div> <div>TITLE:</div> <div>INDIA UNIV; 15A; 32 SRF MNT</div>		
			<div>DIMENSIONS ARE IN INCHES AND [MM]</div>				
			COMMENTS:		<div>SIZE</div> <div>B</div> <div>SCALE: 2:3</div>		
MATERIAL		DWG. NO.		REV			
FINISH		DIN-15R-P532		D			
DO NOT SCALE DRAWING		WEIGHT:		SHEET 1 OF 1			
<div>PROPRIETARY AND CONFIDENTIAL</div> <div>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.</div>							