



STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED

CONN. TYPE	EXTERIOR	INTERIOR
ALL D-SUBS	FEMALE	MALE

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS	
BODY:	EPOXY COATED DIE CAST ALUMINUM	VOLTS:	125V
GASKET:	THERMOPLASTIC ELASTOMER	AMPS:	15A
HANDLE:	POLYAMIDE	SCCR:	10kA
LEVERS:	STAINLESS STEEL	NEMA/UL EN 60529:	4, 12 IP65
UNLESS OTHERWISE SPECIFIED:		PANEL THICKNESS:	5.0mm max
DIMENSIONS ARE IN INCHES AND [MM]		MOUNTING SCREW TORQUE:	0.8N-m
MATERIAL		TERMINAL BLOCK TORQUE:	0.5N-m
FINISH		INCOMING POWER WIRE SIZE:	0.25 - 2.5 sq mm / 24-12AWG
DO NOT SCALE DRAWING		WIRE STRIP LENGTH:	7 - 8 mm
DRAWN BY		MENCOM CORPORATION	
DRAWN DATE		TITLE:	
CHECKED BY		DP-2DB9-32	
CHECK DATE		SIZE	
COMMENTS:		DWG. NO.	
		REV	
		SCALE: 2:3	
		WEIGHT:	
		SHEET 1 OF 1	